



RINGBROTHERS®

E4829 Hwy 14 • Spring Green, WI 53588 • 608.588.7399 • www.ringbrothers.com • marissa@ringbrothers.com

1967-1969 GM Trunk Hinge

Part #8032-20679

Installations Steps:

1. Remove deck lid:
 - a. Place painters tape and or shop towels on any surfaces to protect them from the following steps.
2. Remove torque rods. We recommend wearing safety glasses and gloves during the following steps, the torque rods are under high tension:
 - a. Using a $\frac{1}{4}$ " x 5 $\frac{1}{2}$ " rod on the end of the torque rod pull back slowly to release tension to the next hook.
 - b. Alternating from side to side do this until the rods are removed.
3. Remove hinges.
 - a. To remove the existing hinges the hinge pin shown in Figure 1 will need to be removed. Cutting and or drilling this stud will work. This same hole will be used to bolt your new hinge, try to keep the original shape.



Figure 1: Remove stud

4. Marking for gas struts:
 - a. Referencing Figure 2, measure and mark $\frac{3}{4}$ " from the back edge. This mark will be used to verify the ball stud location.



Figure 2: Ball stud hole

5. Install new hinge:
 - a. Verify that the gas struts are attached to the ball studs and on opposite sides.

